

LEOCH VRLA-AGM BATTERY TERMINAL OPTIONS

A SPLENDID FUTURE THROUGH THE EFFORTS OF ALL

Unit:mm[inch]

T1 Terminal FASTON TYPE (Copper) quick disconnect tabs; silver coating for better conductivity

T2 Terminal FASTON TYPE (Copper) quick disconnect tabs; silver coating for better conductivity

T10 Terminal Lead Torque: 3.9 ~ 5.4 N*m

T11 Terminal Brass Coated With Tin; Threaded Insert 8mm STUD Torque: 11~14.7 N*m

T3 Terminal Brass Coated With Tin Torque: 3.9 ~ 5.4 N*m

T4 Terminal Brass Coated With Tin Torque: 3.9 ~ 5.4 N*m

T12 Terminal Brass Coated With Tin; Threaded Insert 5mm STUD Torque: 2.0 ~ 3.0 N*m

T13 Terminal Brass Coated With Tin; Threaded Insert 6mm STUD Torque: 3.9 ~ 5.4 N*m

T5 Terminal Lead Torque: 3.9 ~ 5.4 N*m

T6 Terminal Brass Coated With Tin; Threaded Insert 6mm STUD Torque: 3.9 ~ 5.4 N*m

T14-1 Positive Lead Torque: 11 ~ 14.7 N*m

T14-2 Negative Lead Torque: 11 ~ 14.7 N*m

T7 Terminal Brass Coated With Tin; Threaded Insert 6mm STUD Torque: 3.9 ~ 5.4 N*m

T9 Terminal Lead Torque: 11 ~ 14.7 N*m

Spring Terminal Spring Steel Fully Collapsible

Connector Toy Battery Connector H-Connector

VALVE REGULATED LEAD-ACID BATTERY, RECHARGABLE

MAINTENANCE-FREE, SEALED WITH AGM SEPARATOR